3.1     GROUND WIRE-XX     GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)     1       3.2     CONNECTOR-XX     CONNECTOR (SIZE & TYPE AS REQUIRED)     2   35-46KV, 1-PHASE PRIMARY DRAWING NO.:					24/25/26/27 (24/25/26/27) (2) (2) (2) (2) (2) (2) (2) (2) (2) (2	
2.1       BM-24       BRACKET - TANGENT MESSENGER, 24"       2         2.2       HPI-25VTP-01       INSULATOR, 25kV, VISE TOP, 1" PIN       1         2.3       SSP-2       INSULATOR, 25kV, VISE TOP, 1" PIN       1         2.4       MBLT5/8-XX       BOLT, MACHINE, 5/8" X REQ. LENGTH       4         2.5       SWSH5/8-XX       WASHER, SQUARE, 5/8 X 2:1/4"       4         2.6       LWSH5/8-XX       WASHER, SPRINGLOCK, 5/8"       4         2.7       SNUT5/8-XX       SQUARE NUT, 5/8"       4         3       SC-H.01G       GROUNDING GUIDE SPACER CABLE       1         3.1       GROUND WIRE-XX       GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)       1         3.2       CONNECTOR-XX       CONNECTOR (SIZE & TYPE AS REQUIRED)       2		NUMBER			4 April 1	R
2.2       HPI-25VTP-01       INSULATOR, 25kV, VISE TOP, 1" PIN       1         2.3       SSP-2       INSULATOR PIN, SHORT SHANK, 3/4" W/1" NYLON THREAD       1         2.4       MBLT5/8-XX       BOLT, MACHINE, 5/8" X REQ. LENGTH       4         2.5       SWSH5/8-XX       WASHER, SQUARE, 5/8 X 2-1/4"       4         2.6       LWSH5/8-XX       WASHER, SPRINGLOCK, 5/8"       4         2.7       SNUT5/8-XX       SQUARE NUT, 5/8"       4         3       SC-H.01G       GROUNDING GUIDE SPACER CABLE       1         3.1       GROUND WIRE-XX       GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)       1         3.2       CONNECTOR-XX       CONNECTOR (SIZE & TYPE AS REQUIRED)       2	2	SC-ZA1.6	35-46kV, 1-PHASE PRIMARY - TANGENT INCLINED INSTALLATION	1		
2.3       SSP-2       INSULATOR PIN, SHORT SHANK, 3/4" W/T NYLON THREAD       1         2.4       MBLT5/8-XX       BOLT, MACHINE, 5/8" X REQ. LENGTH       4         2.5       SWSH5/8-XX       WASHER, SQUARE, 5/8 X 2-1/4"       4         2.6       LWSH5/8-XX       WASHER, SPRINGLOCK, 5/8"       4         2.7       SNUT5/8-XX       SQUARE NUT, 5/8"       4         3       SC-H.01G       GROUNDING GUIDE SPACER CABLE       1         3.1       GROUND WIRE-XX       GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)       1         3.2       CONNECTOR-XX       CONNECTOR (SIZE & TYPE AS REQUIRED)       2	2.2	HPI-25VTP-01	INSULATOR, 25kV, VISE TOP, 1" PIN	1		
2.4         INDECTNONAL         DOLT, INTECTNING, SIG X 12:1/4"         4           2.5         SWSH5/8-XX         WASHER, SQUARE, 5/8 X 2:1/4"         4           2.6         LWSH5/8-XX         WASHER, SPRINGLOCK, 5/8"         4           2.7         SNUT5/8-XX         SQUARE, 10/0, 5/8"         4           3         SC-H.01G         GROUNDING GUIDE SPACER CABLE         1           3.1         GROUND WIRE-XX         GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)         1           3.2         CONNECTOR-XX         CONNECTOR (SIZE & TYPE AS REQUIRED)         2						(000) 010-2040
2.6       LWSH5/8-XX       WASHER, SPRINGLOCK, 5/8"       4         2.7       SNUT5/8-XX       SQUARE NUT, 5/8"       4         3       SC-H.01G       GROUNDING GUIDE SPACER CABLE       1         3.1       GROUND WIRE-XX       GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)       1         3.2       CONNECTOR-XX       CONNECTOR (SIZE & TYPE AS REQUIRED)       2	2.5				KV CLASS: 35-46kV	
3       SC-H.01G       GROUNDING GUIDE SPACER CABLE       1       STEEP GRADE       REVISION: 0         3.1       GROUND WIRE-XX       GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)       1       35-46KV, 1-PHASE PRIMARY       DRAWING NO.:         3.2       CONNECTOR-XX       CONNECTOR (SIZE & TYPE AS REQUIRED)       2       35-46KV, 1-PHASE PRIMARY       DRAWING NO.:	2.6	LWSH5/8-XX	WASHER, SPRINGLOCK, 5/8"		LINE ANGLE: 0-6°	
3.1       GROUND WIRE-XX       GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)       1         3.2       CONNECTOR-XX       CONNECTOR (SIZE & TYPE AS REQUIRED)       2					STEEP GRADE	<b>REVISION: 0</b>
3.2 CONNECTOR-XX (CONNECTOR (SIZE & TYPE AS REQUIRED) 2 TANOCHIT	3.1	GROUND WIRE-XX	GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.)	1		
				_		
3.3     STAPLE-XX     GROUND WIRE STAPLE (SIZE & TYPE AS REQUIRED)     1     1     1     1     1       3.4     GNDASSY-XX     GROUND ASSEMBLY (TYPE AS REQ., NOT SHOWN)     1     1     1     1	3.3 3.4		GROUND WIRE STAPLE (SIZE & TYPE AS REQUIRED)	1		AC1195-02