

| | r | | |
|------|------------------------|---|--------|
| ITEM | HENDRIX PART NUMBER | DESCRIPTION | QTY |
| 1 | POLE-XX | POLE (TYPE, CLASS & LENGTH AS REQ.) | 1 |
| 2 | SC-TC6.3 | 69KV, 3-PHASE PRIMARY - DOUBLE DEADEND, VERTICAL | 1 |
| 2.1 | PSAC-01 | CLAMP - PERMANENT STRINGING, ANGLE SUSPENSION W/ SHACKLE | 1 |
| 2.2 | GUYINSULATOR-10 | STRAIN INSULATOR, GUY, CLEVIS-THIMBLE EYE, 36" LNG, 15,000 LB | 6 |
| 2.3 | DEINS69 | INSULATOR - DEAD END, 69kV | 6 |
| 2.4 | TC | CLEVIS - THIMBLE | 6 |
| 2.5 | CG-0000 | PREFORMED GRIP, CONDUCTORS, COATED (SIZE & KIND AS REQ.) | 6 |
| 2.6 | LP-INS-3 | LINE POST INSULATOR, 69KV | 3 |
| 2.7 | TRUNNION-01 | CLAMP - TRUNNION, FOR LINE POST INSULATORS | 3 |
| 2.8 | EBLT3/4-XX | BOLT, EYE, 3/4" X REQ. LENGTH | 7 |
| 2.9 | MLBT3/4-XX | BOLT, MACHINE, 3/4" X REQ. LENGTH | 6 |
| 2.10 | SWSH3/4-XX | WASHER, SQUARE, 3/4 X 2-1/4" | 20 |
| 2.11 | LWSH3/4-XX | WASHER, SPRINGLOCK, 3/4" | 11 |
| 2.12 | SNUT3/4-XX | SQUARE NUT, 3/4" | 13 |
| 3 | SC-E.01G | GUYING GUIDE, SPACER CABLE | 1 |
| 3.1 | POLEEYE-XX | POLE-EYE PLATE (SIZE AND STRENGTH AS REQUIRED) | 1 |
| 3.2 | GUYSTRAIN-XX | GUY STRAIN (SIZE & TYPE AS REQUIRED) | 1 |
| 3.3 | GUYSTRAND-XX | GUY STRAND (SIZE AND TYPE AS REQUIRED) | AS REQ |
| 3.4 | ANCHORASSY-XX | ANCHOR AND ANCHOR ROD (SIZE AND TYPE AS REQUIRED) | 1 |
| 4 | SC-H.01G | GROUNDING GUIDE SPACER CABLE | 1 |
| 4.1 | CONNECTOR-XX | CONNECTOR (SIZE & TYPE AS REQUIRED) | AS REQ |
| 4.2 | GNDWIRE-XX | GROUND WIRE, COPPER, #6 AWG (MIN) (LENGTH AS REQ.) | AS REQ |
| 4.3 | STAPLE-XX | GROUND WIRE STAPLE (SIZE & TYPE AS REQUIRED) | AS REQ |
| 4.4 | GNDASSY-XX | GROUND ASSEMBLY (TYPE AS REQ., NOT SHOWN) | 1 |

RED ITEMS ARE NOT SUPPLIED BY HENDRIX

AERIAL CABLE SYSTEMS
53 OLD WILTON RD. MILFORD, NH 03055 (603) 673-2040

DESIGN PARAMETERS: KV CLASS: 69kV LINE ANGLE: 7-20°

REVISION: 4

69KV, 3-PHASE PRIMARY DOUBLE DEADEND VERTICAL CONFIGURATION DRAWING NO.: AC1268-05